MARKING APPLICATIONS

MARKER TYPE	LIQUID PAINT					SOLID PAINT – AMBIENT SURFACE															SOLID PAINT – HOT SURFACE								FELT-TIPS							LUMBER MARKING							SPECIALTY								
SURFACE TYPE	VALVE ACTION® PAINT MARKER	PRO-LINE®	PRO-MAX®	BALL PAINT MARKER®	DURA-BALL®	B PAINTSTIK®	B-E PAINTSTIK®	B-L PAINTSTIK®	BL-W PAINTSTIK®	C PAINTSTIK®	E PAINTSTIK®	F PAINTSTIK®	FAST DRY PAINTSTIK®	M PAINTSTIK®	M-10 PAINTSTIK®	N PAINTSTIK®	O-10 PAINTSTIK®	P PAINTSTIK®	WS-3/8 PAINTSTIK®	QUIK STIK® PAINT MARKER	H PAINTSTIK®	HT PAINTSTIK®	HT-34 PAINTSTIK®	HT-40 PAINTSTIK®	HT-75 PAINTSTIK®	J PAINTSTIK®	K PAINTSTIK®	PK PAINTSTIK®	X-5 PAINTSTIK®	DURA-INK® #15	DURA-INK® #20	DURA-INK® #25	DURA-INK® #50	DURA-INK® #80	DURA-INK® #100	PLASTIC TAG MARKER	PRO-EX® CRAYON	LUMBER CRAYON #200	LUMBER CRAYON #500	ULTRASCAN™	OPTIMARK™	SCAN-IT PLUS®	SCAN-IT®	TRADES MARKER®	CHINA MARKER	CARPENTER'S PENCIL	SILVER-STREAK®	RED-RITER®	SOAPSTONE	TYRE MARQUE®	ZEPHYR® PAINTSTIK®	RAILROAD CHALK
METAL																																																				
AMBIENT SURFACE, -50° TO 150°F	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•									•	•	•	•	•	•		•	•	•					•	•		•	•	•		•	•
HOT SURFACE (See p.15 for specific temps.)															•						•	•	•	•	•	•	•	•																							
OIL COVERED	•	•	•	•	•	•	•				•	•	•				•			•																															
ROUGH SURFACE						•	•				•	•	•				•			•																															•
BLEED-THROUGH PRIMER								•	•																																										
HIGH VISIBILITY	•	•	•	•	•						•	•	•																										•												•
FOR GALVANIZING																		•										•																							
NO BLEED-THROUGH																•				•																															
MARKING UNDER BLACK LIGHT												•																														•	•							
ANNEALING AND HEAT TREATING														•	•																																			
WOOD																																																			
DRY LOGS						•	•				•	•								•																•	•	•	•	•	•	•									•
WET LOGS						•	•				•	•								•																•	•	•	•												•
GRADING LUMBER, PLYWOOD																																				•	•	•	•	•	•	•									•
GRADING LUMBER W/BLACK LIGHT READER												•					•																					•	•	•	•	•									
CREOSOTED LUMBER						•	•				•	•																								•															•
HIGH VISIBILITY	•	•	•	•	•						•	•																											•			•	•								
BOXES & CRATES	•	•	•	•	•	•	•				•	•								•									•	•	•	•	•	•		•	•	•	•	•	•	•	•	•	•						•
SURVEYOR'S STAKES	•	•	•	•	•	•	•				•	•								•									•	•	•	•	•	•	•	•	•	•	•	•	•			•	•	•					
PLASTIC																																																			
PIPING & TUBING	•	•	•	•	•	•	•			•	•	•	•						•	•									•	•	•	•	•	•	•									•	•						•	
PLASTIC TAGS																													•	•	•	•	•	•	•																	
INVENTORY TAGS	•	•	•																	•									•	•	•	•	•	•	•									•	•							
BINS & CONTAINERS	•	•	•	•	•	•	•			•	•	•	•							•									•	•	•	•	•	•	•									•	•							
FILM	•	•	•	•	•	•	•			•	•	•	•							•									•	•	•	•	•	•	•									•	•							
SHEET - ROD - SLAB	•	•	•	•	•	•	•			•	•	•	•						•	•									•	•	•	•	•	•	•									•	•						•	
LAMINATES	•	•	•	•	•	•	•			•	•	•	•						•	•									•	•	•	•	•	•	•									•	•						•	
GLASS & CERAMICS																																																			
PERMANENT MARKING	•	•	•	•	•	•	•			•	•	•	•			•				•									•	•	•	•	•	•																		
TEMPORARY MARKING																			•																										•	•						•	
CONCRETE & STONE																																																			
CONCRETE & STONE						•	•				•	•	•							•																•	•	•		•	•	•									•
PAPER																																																			
SIGNS	•	•	•			•	•			•	•	•								•									•	•	•	•	•	•									•	•	•							
WAXED OR COATED	•		•			•	•			•	•	•								•																																
CARDBOARD																																																			
SIGNS	•	•	•			•	•			•	•	•								•									•	•	•	•	•	•		•	•	•					•	•	•							
CARTONS - DRY	•	•	•			•	•			•	•	•								•									•	•	•	•	•	•		•	•	•					•	•	•							•
CARTONS - FROZEN, ICE COVERED						•	•				•	•								•																																•
RUBBER																																																			
AMBIENT SURFACE, -50° TO 150°F	•	•	•	•	•	•	•			•	•	•	•						•	•																•	•		•		•	•	•						•	•	
HOT SURFACE, 300° TO 500°F																								•	•			•																								
CLOTH - FABRICS																																																			
PERMANENT	•	•	•	•	•	•	•			•	•	•	•							•									•	•	•	•	•	•																		
TEMPORARY																			•																				•										•		•	•
	pp. 6-9					pp. 10-15															pp. 16-17								pp. 18-21							pp. 22-25							pp. 26-29								

• = RECOMMENDED USES